



Modelo Model	LPL0620NBA	LPL1240NBA	LPL1550NBA
Tensión entrada nominal Input voltage	230V	230V	230V
Frecuencia entrada nominal Input frequency	50Hz	50Hz	50Hz
Rango de frecuencia de entrada Input voltage range	50Hz-60Hz	50Hz-60Hz	50Hz-60Hz
Potencia Power	20W	40W	50W
Número de LEDs Number of LEDs	120 LEDs SMD	240 LEDs SMD	312 LEDs SMD
Flujo lumínico Lumen	2715Lm	5430Lm	6787Lm
Temperatura de color Color temperature	5000K□	5000K□	5000K□
Ángulo Angle	120°	120°	120°
Largo Length	600mm	1200mm	1500mm
Ancho x alto Width x height	80x65mm	80x65mm	80x65mm
Base y difusor Base and diffuser	Policarbonato / PC		
IP	65	65	65
IK	IK10	IK10	IK10



LPL0620NBA  
LPL1240NBA  
LPL1550NBA

## PANTALLA NBA

### VALE LO QUE CUESTA.

Presentamos una pantalla estanca, robusta, fiable y competitiva. Enfocada para las instalaciones donde se precisa un producto efectivo. Fabricada tanto difusor como cuerpo en policarbonato altamente resistente y con electrónica CE+EMC+ROHS.

### IT'S WORTH WHAT IT COSTS.

We present a waterproof, robust, reliable and competitive screen. Focused on installations where an effective product is required. Made of both the diffuser and the body in highly resistant polycarbonate and with CE + EMC + ROHS electronics.

