



PANTALLA NBA CREPUSCULAR

AUTOMÁTICAMENTE

La pantalla NBA SCR incorpora un sensor crepuscular interno que queda prácticamente imperceptible desde el exterior. Este sensor permite un encendido automático de la luminaria cuando el nivel de luz es inferior al rango ajustado al igual que un apagado automático cuando este nivel es superior a lo deseado.

Muy interesante para activación automática en aparcamientos exteriores, naves con buena aportación de luz natural o muchas otra circunstancias.

AUTOMATICALLY

The SCR screen incorporates an internal twilight sensor that is practically invisible from the outside. This sensor allows automatic lighting of the luminaire when the light level is below the adjusted range, as well as automatic shutdown when it is higher than desired.

Very interesting for automatic activation in outdoor parking lots, warehouses with a good contribution of natural light or many other circumstances.

Modelo Model	LPL0620NBASCR	LPL1240NBASCR	LPL1550NBASCR
Tensión entrada nominal Input voltage	230V	230V	230V
Frecuencia entrada nominal Input frequency	50Hz	50Hz	50Hz
Rango de frecuencia de entrada Input voltage range	50Hz-60Hz	50Hz-60Hz	50Hz-60Hz
Potencia Power	20W	40W	50W
Número de LEDs Number of LEDs	120 LEDs SMD	240 LEDs SMD	312 LEDs SMD
Flujo lumínico Lumen	2715Lm	5430Lm	6787Lm
Temperatura de color Color temperature	5000K□	5000K□	5000K□
Ángulo Angle	120°	120°	120°
Largo Length	600mm	1200mm	1500mm
Ancho x alto Width x height	80x65mm	80x65mm	80x65mm
Base y difusor Base and diffuser	Policarbonato / PC		
IP	65	65	65
Sensor crepuscular integrado Integrated twilight sensor	Sí/Yes	Sí/Yes	Sí/Yes
IK	IK10	IK10	IK10



LPL0620NBASCR
LPL1240NBASCR
LPL1550NBASCR



Sensor Crepuscular
SCRLPL



Videos demostrativos:
www.pritec.com/videos

